

Entire Car Protection MATERIAL SAFETY DATA SHEET

Section 1: Identification

Product Name:

Technician's Choice TEC547BS XPC3™ Step Three: Glamour

Date Prepared: Date of Review/Update: November 2, 2011 November 19, 2012

Product Code: Product Class: TEC547BS

Body Shop Safe Automotive Wax/Polish

Manufacturer/Supplier:

ECP Incorporated

11210 Katherine's Crossing, Suite 100

Woodridge, IL 60517 Telephone: 630-754-4200

Emergency Telephone: CHEMTREC 800-424-9300

Section 2: Hazard Identification

Signs and Symptoms of Exposure:

Eyes: May I

May be irritating to the eyes. Eye contact may cause redness, tearing and a burning sensation.

Skin:

May cause slight irritation.

Ingestion:

Harmful if swallowed. Ingestion may cause nausea and irritation.

Inhalation:

No hazard in normal industrial use.

Medical Conditions Aggravated by Exposure:

Dermatitis may be aggravated by excessive exposure to skin.

HMIS Rating:

Health - 1

Fire - 2

Reactivity - 0

Personal Protection - C

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Section 3: Composition

TLV
1
ailable
ailable
ailable
r

Section 4: First Aid Measures

Eye Contact:

Flush with large amounts of water for 15 minutes. If symptoms develop, seek medical attention.

Skin Contact:

Wash with soap and water.

Ingestion:

Do not induce vomiting. Seek medical attention immediately.

Inhalation:

Move to fresh air.

Section 5: Fire-Fighting Measures

Fire and Explosive Properties: Flash Point:

Flash Point: ~ 40°C TCC Flam Water, foam, dry chemical or carbon dioxide extinguisher

Flammable Limits: LEL / UEL:

Not Available

Extinguishing Media: Protective Equipment:

Not Available.

Section 6: Accidental Release Measures

Steps to be taken if Material is Spilled or Leaked:

Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent. Proper disposal of absorbent is required after use. Avoid runoff into storm sewers and ditches which lead to waterways.

Section 7: Handling and Storage

Precautions to be taken in Handling and Storage:

Keep out of reach of Children. Do not allow to freeze. Store between (35°F) Minimum to (95°F) Maximum.

Section 8: Exposure Controls and Personal Protection

Ventilation:

Good general ventilation should be sufficient to control airborne levels.

Respirator Protection:

NIOSH respirator - in absence of proper environmental controls.

Skin Protection:

Use Nitrile/ Vinyl gloves. Clean, body-covering clothing.

Eye Protection:

Wear safety glasses with side shields or goggles.

Section 9: Physical and Chemical Properties

Boiling Point: Vapor Density: Not Available

Not Available

Specific Gravity: ~0.980 % Volatile: 80-90

Appearance/Odor: Teal Creamy Liquid, Pleasant Odor.

Vapor Pressure (mmHg @ 68°F):

Solubility in Water:

Melting Point: :Hq

Not Available Will mix with water Not Available

~8.5-9.8

Section 10: Stability and Reactivity

Stability: Stable

Materials to Avoid:

Not Available

Hazardous Polymerization: No

Conditions to Avoid:

Combustible liquid. Keep away from heat and open flame.

Hazardous Decomposition Products: Carbon Monoxide and Carbon Dioxide

Section 11: Toxicology Information

IARC, NTP, OSHA Carcinogen:

None

Section 12: Ecological Information

Not Available

Section 13: Disposal Considerations

Waste Disposal:

Dispose of in accordance with federal, state and local regulations.

Section 14: Transport Information

D.O.T. REQUIREMENTS (49CFR 172.101):

Not regulated in quantities less than 119 gallons except when shipped by vessel or aircraft. (29CFR173.150) COMBUSTIBLE LIQUID, N.O.S., COMBUSTIBLE LIQUID, NA1993, III

Section 15: Regulatory Information

RQ (REPORTABLE QUANTITY) 49CFR 172.101:

None

TSCA (Toxic Substances Control Act) Status:

The intentional ingredients of this product are listed.

CERCLA RQ - 40CFR 302.4:

None

SARA 302 COMPONENTS - 40CFR 355 Appendix A:

None

SECTION 311/312 HAZARD CLASS - 40CFR 370.2

Immediate

(X) (X)

Reactive

Sudden Release of Pressure

() ()

Delayed Fire

(X)SARA 313 COMPONENTS - 40CFR 372.65:

None

CALIFORNIA PROPOSITION 65:

None

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

Ingredient Mineral Spirits

64475-85-0 64742-47-8 Max. % By Wt. 15-20 5-10

LD50 Oral Rat - > 34600mg/kg Oral Rat - > 5 g/Kg

Not Established Not Established

LC50

Distillates (petroleum) Hydro Treated Light **Odorless Mineral Spirits** Amorphous Silica

64742-48-9 61790-53-2 1-5 10-15 Not Established Not Established

Not Established Not Established

Section 16: Other Information

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.